

FlatLED

T1

Type	Downlight
Mounting	Recessed
Material	Aluminium
Adjustability	Cardanic/Gimble
El. class / IP	Class III / IP20

Citizen CLL LED

LED Module included

Driver to be ordered separately (see options)

CCT	2700K / 3000K
CRI	Ra80 / Ra90
Luminous flux	2700K - Ra80: 1490lm (114lm/W) 2700K - Ra90: 1170lm (90lm/W) 3000K - Ra80: 1585lm (121lm/W) 3000K - Ra90: 1260lm (97lm/W)
Beam angle	37° lens
Power	13W
Current	350mA
Forward voltage	33.6V(min.) - 36.2V (typ.) - 39.9V (max.)
Cooling	Passive (no fan)
SDCM	3



Options

Driver "Mono 350" non dim.

Driver "Mono" Push/1-10V dim.

Driver "Mono" DALI dim.

Driver "Mono 350" mains

Driver "Duo" non dim.

Driver "Duo" 1-10V/Push/DALI dim.

Driver "Trio/Quattro" universal⁽¹⁾

⁽¹⁾The same driver for non dim., 1-10V dim., DALI dim., Push dim.

On Request

Other RAL colors
3500K or 4000K LED

Design awards / Nominations

1. Nominated - Batibouw Brussels (2013)
2. Awarded - Design Plus (2014)

DESIGN PLUS

powered by: **light+building**

Trapezium springs:

Standard



Boobytrap springs:

On request





FlatLED
T1

Citizen LED (350mA) - 37° Lens + Trapezium springs
 2700K - Ra80 - 13W - 1490lm
 2700K - Ra90 - 13W - 1170lm
 3000K - Ra80 - 13W - 1585lm
 3000K - Ra90 - 13W - 1260lm

A Other RAL colors on request



White Matt Texture Standard

Black Matt texture Standard

White + Black Standard

Anthracite Matt Text. Grey Matt Texture

White + Chrome

Black + Chrome

Black + Gold

Gold

Corten